

CENTRAL INTELLIGENCE AGENCY

CD NO.

DATE DISTR. 1 April 1949

NO. OF PAGES 1

SUPPLEMENT TO
REPORT NO.

25X1

IN TO CIA LIBRARY

- | | <u>Standard Type</u> | <u>Light Type</u> |
|---|----------------------|-------------------|
| Axle system | 1 - 5 - 0 | 1 - 5 - 0 |
| Cylinder bore | 630 mm | 560 mm |
| Stroke | 700 mm | 700 mm |
| Maximum Speed | 80 kw/h | 80 kw/h |
| Diameter of (driving)
front wheel | 1,450 mm | 1,450 mm |
| Diagram of turning
wheel | 850 mm | 850 mm |
| Maximum tractive effort | 21 | 16.5 |
| Steam pressure | 16 atmos. | 16 atmos. |
| Heating surface (total) | 240 sq. m. | 178 sq. m. |
| Water in tender | 32 cubic m. | 32 cubic m. |
| Coal in tender | 17 tons | 13 tons |
| Distance between end
axles of locomotive and
tender | 19,500 mm | 18,600 mm |

- CLASSIFICATION SECRET/CONTROL

CLASSIFICATION				SECURITY CONTROL															
STATE #	<input checked="" type="checkbox"/>	NAVY		<input checked="" type="checkbox"/>	NORC		DISTRIBUTION												
ARMY #	<input checked="" type="checkbox"/>	AIR	<input checked="" type="checkbox"/>	FBI															

EXPLOITED BY 4A